

# Max-Sum Inference Algorithm

Sargur Srihari  
srihari@cedar.buffalo.edu

# The max-sum algorithm

- Sum-product algorithm
  - Takes joint distribution expressed as a factor graph
  - Efficiently finds marginals over component variables
- Max-sum addresses two other tasks
  1. Setting of the variables that has the highest probability
  2. Find value of that probability
- Algorithms are closely related
  - Max-sum is an application of dynamic programming to graphical models

# Finding latent variable values having high probability

- Consider simple approach
  - Use sum-product to obtain marginals  $p(x_i)$  for every variable  $x_i$
  - For each variable find value  $x_i^*$  that maximizes marginal
- This would give set of values that are individually most probable
- However we wish to find vector  $x^{\max}$  that maximizes joint distribution, i.e.

$$x^{\max} = \arg_x \max p(x)$$

- With join probability  $p(x^{\max}) = \max_x p(x)$

# Example

- Maximum of joint distribution
  - Occurs at  $x=1, y=0$
  - With  $p(x=1, y=0)=0.4$
- Marginal  $p(x)$ 
  - $p(x=0) = p(x=0, y=0) + p(x=0, y=1) = 0.6$
  - $p(x=1) = p(x=1, y=0) + p(x=1, y=1) = 0.4$
- Marginal  $p(y)$ 
  - $P(y=0)=0.7$
  - $P(y=1)=0.3$
- Marginals are maximized by  $x=0$  and  $y=0$  which corresponds to  $0.3$  of joint distribution
- In fact, set of individually most probable values can have probability zero in joint

$p(x,y)$	$x=0$	$x=1$
$y=0$	0.3	0.4
$y=1$	0.3	0.0

# Max-sum principle

- Seek efficient algorithm for
  - Finding value of  $x$  that maximizes  $p(x)$
  - Find value of joint distribution at that  $x$

- Second task is written

$$\max_x p(x) = \max_{x_1} \dots \max_{x_M} p(x)$$

where  $M$  is total number of variables

- Make use of distributive law for max operator
  - $\max(ab, ac) = a \max(bc)$
  - Which holds for  $a \geq 0$
  - Allows exchange of products with maximizations

# Chain example



- Markov chain joint distribution has form

$$p(x) = \frac{1}{Z} \psi_{1,2}(x_1, x_2) \psi_{2,3}(x_2, x_3) \dots \psi_{N-1,N}(x_{N-1}, x_N)$$

- Evaluation of probability maximum has form


$$\max_x p(x) = \frac{1}{Z} \max_{x_1} \dots \max_{x_N} \psi_{1,2}(x_1, x_2) \psi_{2,3}(x_2, x_3) \dots \psi_{N-1,N}(x_{N-1}, x_N)$$

- Exchanging max and product operators

$$\max_x p(x) = \frac{1}{Z} \max_{x_1} \left[ \psi_{1,2}(x_1, x_2) \left[ \dots \max_{x_N} \psi_{N-1,N}(x_{N-1}, x_N) \right] \right]$$

– Results in

- More efficient computation
- Interpreted as messages passed from node  $x_N$  to node  $x_1$

 The image cannot be displayed. Your computer may not have enough memory to open the image, or the image may have been corrupted. Restart your computer, and then open the file again. If the red x still appears, you may have to delete the image and then insert it again.

# Generalization to tree factor graph

- Substitution factored graph expansion

$$p(x) = \prod_s f_s(x_s)$$

- Into  $\max_x p(x) = \max_{x_1} \dots \max_{x_M} p(x)$
- And exchanging maximizations with products
- Final maximization is performed over product of all messages arriving at the root node
- Could be called the *max-product* algorithm

# Use of log probabilities

- Products of probabilities can lead to numerical underflow problems
- Convenient to work with logarithm of joint distribution
- Has the effect of replacing products in max-product algorithm with sums
- Thus we obtain the *max-sum* algorithm



# Message Passing formulation

- In sum-product we had

From factor  
node to  
variable node

$$\mu_{f \rightarrow x}(x) = \sum_{x_1} \dots \sum_{x_M} f(x, x_1, \dots, x_M) \prod_{m \in \text{ne}(f) \setminus x} \mu_{x_m \rightarrow f}(x_m)$$

From variable  
Node to  
factor node

$$\mu_{x \rightarrow f}(x) = \prod_{l \in \text{ne}(x) \setminus f} \mu_{f_l \rightarrow x}(x)$$

Initial messages sent  
by leaf nodes

$$\begin{aligned} \mu_{x \rightarrow f}(x) &= 1 \\ \mu_{f \rightarrow x}(x) &= f(x) \end{aligned}$$

- By replacing sum with max and products with sums of logarithms

$$\mu_{f \rightarrow x}(x) = \max_{x_1, \dots, x_M} \left[ \ln f(x, x_1, \dots, x_M) + \sum_{m \in \text{ne}(f) \setminus x} \mu_{x_m \rightarrow f}(x_m) \right]$$

$$\mu_{x \rightarrow f}(x) = \sum_{l \in \text{ne}(x) \setminus f} \mu_{f_l \rightarrow x}(x)$$

Initial messages sent  
by leaf nodes

$$\begin{aligned} \mu_{x \rightarrow f}(x) &= 0 \\ \mu_{f \rightarrow x}(x) &= \ln f(x) \end{aligned}$$

# Maximum computation

- At root node in **sum-product** algorithm

$$p(x) = \prod_{s \in ne(x)} \mu_{f_s \rightarrow x}(x)$$

- By analogy in **max-sum** algorithm

$$p^{\max} = \sum_{s \in ne(x)} \mu_{f_s \rightarrow x}(x)$$

# Finding variable configuration with maximum value

- In evaluating  $p^{max}$  we will also get  $x^{max}$  for the most probable value for the root node as

$$x^{max} = \arg \max_x \sum_{s \in ne(x)} \mu_{f_s \rightarrow x}(x)$$

- It is tempting to apply the above to from the root back to leaves
  - However there may be multiple configurations of  $x$  all of which give rise to maximum value of  $p(x)$ 
    - Recursively repeated at every node
  - So over all configuration need not be the one that maximizes

# Modified message passing

- Different type of message passing from the root node to the leaves
- Keeping track of which values of the variables give rise to the maximum state of each variable
- Storing quantities given by


$$\varphi(x_n) = \arg \max_{x_{n-1}} [\ln f_{n-1,n}(x_{n-1}, x_n) + \mu_{x_{n-1} \rightarrow f_{n-1,n}}(x_n)]$$

- Understood better by looking at lattice or trellis diagram

# Lattice or Trellis Diagram

- $k=2$  and  $k=3$  each represent possible values of  $x_N^{max}$
- Two paths give global maximum
  - Can be found by tracing back along opposite direction of arrow

Not a graphical model  
Columns represent variables  
Row represent states of variable



# Backtracking in Trellis

- For each state of given variable there is a unique state of the previous variable that maximizes probability
  - ties are broken systematically or randomly
- Equivalent to propagating a message back down the chain using

$$x_{n-1}^{\max} = \phi(x_n^{\max})$$

- Known as backtracking

# Extension to general tree graphs

- Method is generalizable to tree-structured factor graphs
- If a message is sent from a factor node  $f$  to a variable node  $x$ 
  - Maximization is performed over all other variable nodes  $x_I, \dots, x_N$  that are neighbors of the factor node
- Keeping track of which values of the variables gave the maximum

# Viterbi Algorithm

- Max-sum algorithm gives exact maximizing configuration for variables provided factor graph is a tree
- Important application is in finding most probable sequence of hidden states in a HMM
  - known as the *Viterbi algorithm*



# Max sum versus ICM

- ICM is simpler
- Max sum finds global maximum for tree graphs
- ICM is not guaranteed to find global maximum

# Exact inference in general graphs

- Sum-product and max-sum algorithms
  - are efficient and exact solutions
    - to inference problems in tree-structured graphs
- In some cases we need to deal with graphs with loops
- Message passing framework can be generalized to arbitrary graph topologies
- Known as *junction tree* algorithm

# Junction Tree Algorithm

- **Triangulation:**
  - Find chord-less Cycles such as ACBDA and add links such as AB or CD
- **Join tree**
  - Nodes correspond to maximal cliques of triangulated graph
  - Links connect pairs of cliques that have variables in common
  - Done so as to give a maximal spanning tree defined as
    - Weight of the tree is maximum
    - Weight is sum of weights for links
- **Junction tree**
  - Tree is condensed so that any clique that is a subset of another clique is absorbed
- **Tow-stage message passing algorithm**
  - equivalent to sum-product, can be applied to junction tree
  - to find marginals and conditionals

